

**ISSUED IN ACCORDANCE WITH**  
**Construction Product Regulation 305/2011/EEC**

<b>Product Identification:</b>	Preload Structural Bolting Assemblies
<b>Product Size:</b>	M12 ~ M36
<b>Bolt Grade/Type:</b>	10.9 HV
<b>Nut Grade/Type:</b>	10 HV
<b>Washer Grade/Type</b>	H, HN, HB & H10
<b>Product Finish:</b>	Plain Oiled
<b>Intended Use of Product:</b>	High Strength Structural Bolting Assemblies
<b>Product Standard:</b>	BS EN 14399 Parts 1-9
<b>Manufacturer:</b>	Dinstock Ltd
<b>Manufacturer Address:</b>	Hortonwood 10, Telford, Shropshire TF1 7ES United Kingdom
<b>Verification of constancy:</b>	Attestation System 2+
<b>Harmonised Standard</b>	BS EN 14399-1:2005
<b>Notified Body:</b>	Lloyd's Register Verification Limited 71, Fenchurch Street London EC3M 4BS
<b>LRV Notified Body Number:</b>	0038

Lloyd's Register Verification Limited performed initial determination of the product type on the basis of type testing, and initial inspection of factory production control and carry out continuous surveillance, assessment and evaluation of factory production control in accordance with the requirements of attestation system 2+ and have issued:

**Factory Production Control Certificate Number: 0038/CPR/LRQ 4006330/B**

<b>BOLT</b>									
<b>Essential Characteristics</b>	<b>Performance:</b>								<b>Harmonised Technical Specification:</b>
	<b>M12</b>	<b>M16</b>	<b>M20</b>	<b>M22</b>	<b>M24</b>	<b>M27</b>	<b>M30</b>	<b>M36</b>	
% Elongation after Fracture	9.0% (Minimum)								EN14399-1:2005 (ISO898-1:2013)
Tensile Strength	1040 MPa (Minimum)								EN14399-1:2005 (ISO898-1:2013)
Stress at 0.2% non prop Elongation	940 MPa (Minimum)								EN14399-1:2005 (ISO898-1:2013)
Stress under Proof Load	830 MPa (Minimum)								EN14399-1:2005 (ISO898-1:2013)
Strength under Wedge Load	Pass with 6°								EN14399-1:2005 (ISO898-1:2013)
Hardness	320~380 HV								EN14399-1:2005 (ISO898-1:2013)
Impact Strength	27J at -20°C (Minimum)								EN14399-1&4:2005 (EN10045-1)
Release of Dangerous Substances									NPD
Durability (Corrosion Protection)									NPD

<b>NUT</b>									
<b>Essential Characteristics</b>	<b>Performance:</b>								<b>Harmonised Technical Specification:</b>
	<b>M12</b>	<b>M16</b>	<b>M20</b>	<b>M22</b>	<b>M24</b>	<b>M27</b>	<b>M30</b>	<b>M36</b>	
Proof Load	88,500 N	164,900 N	259,700 N	321,200 N	374,200 N	486,500 N	594,700 N	866,000 N	EN14399-1&4:2005
Hardness	272~353 HV								EN14399-1&4:2005(ISO898-2:2012)
Release of Dangerous Substances									NPD
Durability (Corrosion Protection)									NPD

WASHERS									
Essential Characteristics	Performance:								Harmonised Technical Specification:
	M12	M16	M20	M22	M24	M27	M30	M36	
Hardness Part 6	300~370 HV								EN14399-1&6:2005
Hardness Part 9 (Nut Faced & Bolt Faced)	38~45 HRC								EN14399-1&9:2005
Hardness Part 9 (DTI)	380 HV (Maximum)								EN14399-1&9:2005
Compression Part 9 (DTI)	59~71 kN	110~132 kN	172~206 kN	212~254 kN	247~296 kN	321~385 kN	393~472 kN	572~688 kN	EN14399-1&9:2005
Release of Dangerous Substances									NPD
Durability (Corrosion Protection)									NPD

ASSEMBLIES									
Essential Characteristics	Performance:								Harmonised Technical Specification:
	M12	M16	M20	M22	M24	M27	M30	M36	
Tensile Resistance of Assembly (Minimum)	59.0 kN	109.9 kN	171.5 kN	212.0 kN	247.0 kN	321.0 kN	392.7 kN	571.9 kN	EN14399-2:2005
Durability (Corrosion Protection)									NPD
K-class	K0								EN14399-1,2,4,6&9:2005

Dinstock Ltd hereby confirm that the products identified conform with the declared performance as set out above.

**This declaration of performance is issued under the sole responsibility of Dinstock Ltd.**

Signed on behalf of Dinstock Ltd:



Name: Robert Pearson

Position: Director

Date: 08/05/2014