

| WASHERS | | | | | | | | | | | | |
|--------------------------------------|-------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------------------------------------|
| Essential Characteristics | Performance: | | | | | | | | | | | Harmonised Technical Specification: |
| | M12 | M14 | M16 | M18 | M20 | M22 | M24 | M27 | M30 | M33 | M36 | |
| Hardness | 100 HV (Minimum) | | | | | | | | | | | EN15048-1:2007 (ISO6507-1:2005) |
| Release of Dangerous Substances | | | | | | | | | | | | NPD |
| Durability (Corrosion Protection) | Minimum coating thickness 3 microns | | | | | | | | | | | EN15048-1:2007 (ISO4042:2000) |

| ASSEMBLIES | | | | | | | | | | | | |
|---|-------------------------------------|---------|----------|----------|----------|----------|----------|----------|----------|----------|----------|-------------------------------------|
| Essential Characteristics | Performance: | | | | | | | | | | | Harmonised Technical Specification: |
| | M12 | M14 | M16 | M18 | M20 | M22 | M24 | M27 | M30 | M33 | M36 | |
| Tensile Resistance of Assembly (Minimum) | 70.0 kN | 95.5 kN | 130.0 kN | 159.0 kN | 203.0 kN | 252.0 kN | 293.0 kN | 381.0 kN | 466.0 kN | 576.0 kN | 678.0 kN | EN15048-1:2007 |
| Durability (Corrosion Protection) | Minimum coating thickness 3 microns | | | | | | | | | | | EN15048-1:2007 (ISO4042:2000) |

Dinstock Ltd hereby confirm that the products identified conform with the declared performance as set out above.

This declaration of performance is issued under the sole responsibility of Dinstock Ltd.

Signed on behalf of Dinstock Ltd:



Name: Robert Pearson

Position: Director

Date: 08/05/2014