

<b>WASHERS</b>												
<b>Essential Characteristics</b>	<b>Performance:</b>											<b>Harmonised Technical Specification:</b>
	<b>M12</b>	<b>M14</b>	<b>M16</b>	<b>M18</b>	<b>M20</b>	<b>M22</b>	<b>M24</b>	<b>M27</b>	<b>M30</b>	<b>M33</b>	<b>M36</b>	
Hardness	100 HV (Minimum)											EN15048-1:2007 (ISO6507-1:2005)
Release of Dangerous Substances												NPD
Durability (Corrosion Protection)	Minimum coating thickness 6 microns											EN15048-1:2007 (BSENISO10683:2014)

<b>ASSEMBLIES</b>												
<b>Essential Characteristics</b>	<b>Performance:</b>											<b>Harmonised Technical Specification:</b>
	<b>M12</b>	<b>M14</b>	<b>M16</b>	<b>M18</b>	<b>M20</b>	<b>M22</b>	<b>M24</b>	<b>M27</b>	<b>M30</b>	<b>M33</b>	<b>M36</b>	
Tensile Resistance of Assembly (Minimum)	87.7 kN	120.0 kN	163.0 kN	200.0 kN	255.0 kN	315.0 kN	367.0 kN	477.0 kN	583.0 kN	722.0 kN	850.0 kN	EN15048-1:2007
Durability	Minimum coating thickness 6 microns											EN15048-1:2007 (BSENISO10683:2014)

Dinstock Ltd hereby confirm that the products identified conform with the declared performance as set out above.

**This declaration of performance is issued under the sole responsibility of Dinstock Ltd.**

Signed on behalf of Dinstock Ltd:



Name: Robert Pearson

Position: Director

Date: 08/05/2014