

<b>WASHERS</b>												
<b>Essential Characteristics</b>	<b>Performance:</b>											<b>Harmonised Technical Specification:</b>
	<b>M12</b>	<b>M14</b>	<b>M16</b>	<b>M18</b>	<b>M20</b>	<b>M22</b>	<b>M24</b>	<b>M27</b>	<b>M30</b>	<b>M33</b>	<b>M36</b>	
Hardness	100 HV (Minimum)											EN15048-1:2007 (ISO6507-1:2005)
Release of Dangerous Substances												NPD
Durability (Corrosion Protection)	Minimum coating thickness 6 microns											EN15048-1:2007 (BSENISO10683:2014)

<b>ASSEMBLIES</b>												
<b>Essential Characteristics</b>	<b>Performance:</b>											<b>Harmonised Technical Specification:</b>
	<b>M12</b>	<b>M14</b>	<b>M16</b>	<b>M18</b>	<b>M20</b>	<b>M22</b>	<b>M24</b>	<b>M27</b>	<b>M30</b>	<b>M33</b>	<b>M36</b>	
Tensile Resistance of Assembly (Minimum)	<b>70.0 kN</b>	<b>95.5 kN</b>	<b>130.0 kN</b>	<b>159.0 kN</b>	<b>203.0 kN</b>	<b>252.0 kN</b>	<b>293.0 kN</b>	<b>381.0 kN</b>	<b>466.0 kN</b>	<b>576.0 kN</b>	<b>678.0 kN</b>	EN15048-1:2007
Durability (Corrosion Protection)	Minimum coating thickness 6 microns											EN15048-1:2007 (BSENISO10683:2014)

Dinstock Ltd hereby confirm that the products identified conform with the declared performance as set out above.

**This declaration of performance is issued under the sole responsibility of Dinstock Ltd.**

Signed on behalf of Dinstock Ltd:



Name: Robert Pearson

Position: Director

Date: 08/05/2014