



EC Declaration of Performance

BS EN 15048 Parts 1 & 2

Declaration of Performance No. DIN00112/1

Page 3 of 3

WASHERS												
Essential Characteristics	Performance:											Harmonised Technical Specification:
	M12	M14	M16	M18	M20	M22	M24	M27	M30	M33	M36	
Hardness	100 HV (Minimum)											EN15048-1:2007 (ISO6507-1:2005)
Release of Dangerous Substances												NPD
Durability (Corrosion Protection)	Minimum coating thickness 3 microns											EN15048-1:2007 (ISO4042:2000)

ASSEMBLIES												
Essential Characteristics	Performance:											Harmonised Technical Specification:
	M12	M14	M16	M18	M20	M22	M24	M27	M30	M33	M36	
Tensile Resistance of Assembly (Minimum)	87.7 kN	120.0 kN	163.0 kN	200.0 kN	255.0 kN	315.0 kN	367.0 kN	477.0 kN	583.0 kN	722.0 kN	850.0 kN	EN15048-1:2007
Durability	Minimum coating thickness 3 microns											EN15048-1:2007 (ISO4042:2000)

Dinstock Ltd hereby confirm that the products identified conform with the declared performance as set out above.

This declaration of performance is issued under the sole responsibility of Dinstock Ltd.

Signed

on behalf of Dinstock Ltd:

Name: Steven Paskin

Position: Director

Date: 01/04/2024